

Gloria HX-1530 TC Table Changer

THE SEAL OF ASSURANCE



The HX-1530 fitted with an exchange table so an operator loads and unloads one pallet while the beam keeps cutting on the other. Laser power, head and motion specifications match the base HX, but throughput rises because the machine is not idle during material handling. The right configuration when loading time, not laser power, is the constraint on output.

SPECIFICATIONS

Laser power	1.5 / 2 / 3 kW	Working area	1500 x 3000 mm (standard; up to 2000 x 8000 mm)
Table system	Dual exchange table changer	Laser source	IPG / Raycus fiber
Wavelength	1080 nm	Cutting head	Bochu
Max cutting speed	40 m/min	Max travelling speed	70 m/min
Position accuracy	< +/-0.04 mm	Min line width	< 0.12 mm
Acceleration	1.5 G	Cooling	Water cooling
Drive	AC servo motor	Working voltage	AC 420V

APPLICATIONS

High-throughput sheet cutting · Continuous production runs · Reduced loading downtime

INDUSTRIES

Metal fabrication · Signage · General engineering · Contract manufacturing

ENQUIRE

WhatsApp / Email
enquiries@rikosys.com

Base
ANC Free Zone, Ajman, UAE

Request
Ask for a quote or full spec